



# PERFORMANCE EXHAUST

A PerTronix Performance Brand ~ [www.pertronixbrands.com](http://www.pertronixbrands.com) ~ 909 599-5955

## Installation Instructions & Warranty Information

40-9021 ~ 2016-17 Toyota Tacoma 3.5L V6  
Cat Back Exhaust



4

This product is considered a Replacement part per CARB and EPA regulations for emissions compliance and is legal for sale and use on all vehicles in all 50 states when installed according to the Manufacturer's Application Guide and Installation Instructions.

**⚠ WARNING:**

This product can expose you to chemicals including Lead, Nickel, Cadmium and Chromium which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## ***PLEASE READ BEFORE PROCEEDING***

PerTronix® thanks you for choosing a JBA Performance Exhaust Product. To realize the potential of JBA's engineering and excellent fit, Please Read and Understand these instructions completely prior to starting the installation.

Check that you received all the parts listed on the parts list, if you have any concerns, please contact PerTronix before continuing.

Work Smart – Work Safe! Most Exhaust Installations are best performed on a lift. If a lift is not available, raise the vehicle and support on quality Jack Stands on level ground. Do not rely on a jack!

Before starting, allow the vehicle to cool, disconnect the battery, and spray penetrating oil on all hardware and fittings that will need to be removed. Silicone spray on rubber hangers will make them easier to remove and install.

1. Spray WD40 or similar on all bolts and the rubber hangers, remove the rubber hangers from the factory exhaust system. While supporting the muffler, unbolt the two bolts that connect the exhaust pipe to the factory connector pipe. Save the two bolts and springs as they will be re used.
2. The entire exhaust system will now come out as one piece from the front.
3. Install the JBA Front 'S' Shape pipe to the factory flange. Make sure the gasket is in good shape, if not get a new one from Toyota.
4. Slip the Muffler onto the front pipe with the centered inlet facing forward, and use the U Bolt clamp with the single hanger to mount the muffler, inserting the hangers into the rubber mounts. Do Not tighten the clamp at this point, leave snug.
5. Slip the over axle pipe into position inserting the rear hanger into the factory rubber mount and the front of the pipe into the muffler. Insert the U Bolt Clamp with the Dual Hangers into the factory rubber hangers and clamp the muffler to the pipe.
6. Align the Muffler and over Axle pipe so the tip is at least 1" from the body and the rear leaf spring mount. When you are satisfied with the alignment, tighten all the clamps.
7. Start the truck and check for leaks. Re-Check all clamps after 100 miles and periodically thereafter.
8. JBA recommends that you tack weld all joints to keep them from slipping or rotating with driving use.

Parts List:

1 Flanged Front 'S' Pipe  
1 Over Axle Pipe with Tip

1 JBA Performance Muffler  
2 2 1/2" U Bolt Clamp with Hangers

### **JBA LIMITED WARRANTY**

All JBA Headers and Exhaust products are guaranteed, to the original purchaser, to be free of defects in materials and workmanship for one year. This warranty covers the replacement or repair of the product only and does not cover the cost of removal and installation, customer applied aftermarket coatings or any discoloration or corrosion of finished surfaces.

Damage or product failure resulting from collision, improper installation, off-road use, road hazards, the use of exhaust insulating wrap or like products or rust occurring after installation, is not covered by the warranty. The warranty extends only to the original purchaser.

Should a part become defective it should be returned to the original selling retailer and must be accompanied with the sales receipt. If there is no retailer in your area, call the factory for a return authorization and return your part prepaid to the factory for inspection. PerTronix reserves the rights to replace or repair the alleged defective part and return the part freight collect.