



2111HKR (Painted) & 2111-1HKR (Ceramic)

SUPER COMPETITION CHEVY HEADERS

67-69 Camaro, 68-72 Chevy II or Nova

SUPER COMPETITION ENGINE SWAP CHEVY HEADERS

73-74 Chevy II or Nova

(396-502)

NOTE: Will not fit with air conditioning or air pump.

Thank you for making HOOKER HEADERS your choice in a high-performance exhaust system. Extensive dyno/track testing has enabled HOOKER to offer the most advanced design in exhaust systems. The installation, while not complex, will take a certain amount of time. However, the additional horsepower and improved performance will more than justify your efforts. Proper installation and maintenance will ensure long life and maximum performance from your hooker exhaust system.

WARNING! Breaking in an engine with ceramic-coated headers WILL result in damage to the coating and will VOID all warranties. Ceramic-coated headers require several heat cycles to fully cure before they will withstand extreme heat. HOOKER recommends using a cast-iron exhaust manifold or an old header to break in new engines to avoid coating damage.

BEFORE STARTING

Your vehicle must be raised a minimum of 36 inches. A floor hoist is ideal. If no hoist is available, we strongly urge the use of axle stands as a safety measure.

CAUTION! YOUR CAR SHOULD NOT BE SUPPORTED ON A BUMPER JACK.

INSTALLATION PROCEDURE – PLEASE READ CAREFULLY

LEFT SIDE

1. Disconnect the battery cable to prevent damage to the electrical system.
2. Unbolt the headpipe from the exhaust manifold and push aside.
3. Remove the clutch linkage, oil filter, spark plugs, and stock exhaust manifold.
4. On 69-70 standard transmission equipped cars, remove the bell crank and lower rod from the transmission locking device.
5. Starting from below, work the header up through the chassis into position.
6. Place gasket into position and start all bolts (most restricted first).
NOTE: If equipped with a smog pump, remove the injection tubes from the stock exhaust manifold and install in the header. See Figure A.
7. Tighten all bolts evenly.
8. Replace clutch linkage, oil filter, and spark plugs.

RIGHT SIDE

1. Unbolt the headpipe from the stock exhaust manifold and push aside.
2. Remove the spark plugs, stock exhaust manifold, and starter.
3. Starting from below, work the header up through the chassis into position.
4. Place gasket into position and start all bolts (most restricted first).
NOTE: If equipped with a smog pump, remove the injection tubes from stock exhaust manifold and install in the header. See Figure A.
5. Replace the spark plugs. Reinstall the starter and tighten all bolts evenly.
6. To connect the collectors to the headpipes, purchase Hooker Header Reducer Kit No. 11035HKR.
NOTE: A dual exhaust system can be fabricated using Hooker Competition Turbos #21005HKR or #21006HKR and a universal tailpipe.
7. Connect the battery, start the engine, and check for leaks. Be sure all brake lines, fuel lines, and electrical wires have sufficient clearance. Reroute as necessary.

When finished, give your car a test drive checking carefully for any new noises. After several days driving, retighten all bolts.

NOTE: Big block engine frame stands and engine mounts must be used to insure proper fit of header. Frame stands and engine mounts are available through (Rick's First Gen., 420 Athena Drive, Athens GA. 30601; phone #1-800-359-7717; www.firstgen.com)

Any questions? Please contact Technical Service: 1-866-464-6553 or 270-781-9741. For online help, please refer to the website: www.holley.com.

See back of page for Figure A




Figure A

LIMITATION OF LIABILITY – DISCLAIMER:

The regulation of emissions production, noise levels, and safety standards is undertaken by the federal government, each of the fifty state legislatures, and by many local municipalities, towns, and counties.

HOKER makes no warranties of merchantability, of fitness for particular purpose, or that its products are approved for general use, or that its products are approved for general use, or that its products comply with laws, regulations, or ordinances in the state where they may be sold to the ultimate purchaser, the consumer.

Unless expressly stated to the contrary in the catalog, instruction sheet; or price list, the entire risk as to the conformity of any company product in any such state and as to repair should the product prove to be defective or non-conforming, is on the retail purchaser, the buyer, the ultimate consumer, of such product and it is not upon the seller, distributor, or manufacturer.

In this connection, the retail purchaser, the buyer, the ultimate consumer assumes the burden of the entire cost of any and all necessary service, alterations, or repair.

THE FOREGOING STATEMENT LIMITS THE LIABILITY OF THE MANUFACTURER.

California vehicle code, sections 27156 and 38391, prohibits the advertising, offering for sale, or installation of any device, which modifies a vehicle's emission control system, unless exempted, unless otherwise noted. HOKER™ Headers that have not received an Executive Order (E.O.) exemption from these code sections are not legal for sale or use in California on vehicles originally equipped with catalytic converters, except for racing vehicles, which may never be driven upon a highway. Check with your local authorities to determine if these headers are legal for use in your particular area.

2111HKR-INST

Revision Date: 5-21-19